

NOTES:

- 1. ALL FLANGE PLATES SHALL BE VERTICAL.
- 2. MAST ARMS WITH LENGTHS < = 50' SHALL HAVE A 3° RISE IN THE ARM ONLY.
- 3. MAST ARMS WITH LENGTHS >= 60' AND <= 70' SHALL HAVE A 4° RISE IN THE ARM ONLY
- 4. ARM RISES SHOULD BE FABRICATED WITHOUT DEAD LOAD DEFLECTION.
- 5. ARM PLATE AND POLE PLATE MATING SURFACES SHALL BE IN THE SAME PLANE TO WITHIN 16".

ARM SIZE:						FLANGE BOLTS
THICKNESS X BUTT DIAMETER	х	Y	τ	P	P 2	(ALL BOLTS SHALL HAVE A CLASS OF FIT RATING OF 2A/2B UNC)
SEVEN (7) GAUGE - 9" DIA.	14"	61/2"	1/4"	1 1/4"	21/2"	11/4" DIA. x 4" LENGTH SEVEN (7) THREADS / IN. WITH FLAT WASHER
THREE (3) GAUGE - 10" DIA.	14"	18"	1,4"	1 1/2"	3 "	1½" DIA. x 5" LENGTH SIX (6) THREADS / IN. WITH FLAT WASHER
THREE (3) GAUGE - 121/2" DIA.	13"	6 1/2"	3/8"	2 "	21/2"	1 ¹ ⁄4" DIA. x 6 ¹ ⁄2" LENTH SIX (6) THREADS / IN. WITH FLAT WASHER

